

RECESSED SMOOTH FACE BATTEN

M333S-60



Leaders in Innovative Building Products

PRODUCT DESCRIPTION

A smooth face batten for use in composite cladding applications. The recessed centre of this furring channel allows for the channel to be fixed at its centre without the fixing extending beyond the face of the channel.

FEATURES

- Made from high quality, Australian steel.
- 13mm deep low profile for direct fixing.
- Suits Double Sided Tape

INSTALLATION

- Contact Studco's technical team for custom solutions on 1300 255 255 or email techadvice@studcosystems.com.au

APPLICATION

For use within composite cladding applications.

PRODUCT RANGE

Ordering Information

Product Code	Product Info	Width (mm)	Depth/Height (mm)	Length (mm)	Thickness BMT (mm)	Sub Pack	Stock Pack	Approx Kg / Piece
M333S-60	Recessed Smooth face Batten	118	13	6000*	0.50	10	200	0.52

*Lead times may apply

WARRANTY

This product is covered by Studco's Warranty.

Conditions and limitations of warranties are set out in Studco Project Warranty certificate.

FURTHER ASSISTANCE

Contact the Technical Team at Studco for assistance with specifications, product selection, acoustic engineering, and structural engineering enquiries. Call on 1300 255 255 or contact us at sales@studcosystems.com.au.



M333S-60



ACCREDITATION



For Sales Enquiries, please contact Studco Building Systems on 1300 255 255